

SPECIFICATIONS:
ELECTRICAL


CONTACT RESISTANCE: 40 mΩ OHMS MAX.
INSULATION RESISTANCE: 1000 MEGA OHMS MINIMUM, 500V DC
VOLTAGE BREAKDOWN: 1000 V AC FOR 1 MINUTE

MECHANICAL


HOUSING: UL94V0 GRADE HIGH TEMP PBT
HOUSING COLOUR: BLACK
CONTACT MATERIAL: PHOSPHOR BRONZE 0.46 DIA.
CONTACT PLATING: GOLD - 03, 06, 15, 30 OR 50 U"
 (MICRO INCHES) OVER NICKEL
OPERATING LIFE: 600 MATING CYCLES

PART NO:

JP-S1-8P××-0××
 GOLD PLATING
 03, 06, 15, 30 OR 50 MICRO INCHES
 OPEN BODY - LOW PROFILE
 4C, 6C, 8C NO. OF CONTACTS LOADED



RECOMMENDED PCB LAYOUT
FOR 8P8C



RECOMMENDED PCB LAYOUT
FOR 8P6C

PRAN ELECTRONICS PVT. LTD.
 52, GIDC, MAKARPURA,
 VADODARA, INDIA. TEL: 91-265-2632916