



**SPECIFICATIONS:
ELECTRICAL**

CONTACT RESISTANCE : 40 mΩ maximum.

INSULATION RESISTANCE: 1000 MΩ minimum. 500 V DC.

PROOF VOLTAGE : 1000 V AC for 1 minute.

MECHANICAL

HOUSING : PBT - Glass filled UL94V0.

HOUSING COLOUR : Black.

CONTACT MATERIAL : Phosphor Bronze 0.46 dia.

PLATING : Gold Plating 3, 6, 15, 30, or 50U".

OPERATING LIFE : 600 mating cycles minimum.

PART NO.

JP-T1-8P8C-03 Gold Plating: 03, 06, 15, 30, or 50U"

_____ No. of contacts 2C, 4C, 6C, 8C

Part Name:	Material:	Revision No: 00	Sheet 1 of 1
1. Housing	PBT UL94V0	Design by: <i>AKH</i>	Date: 04/5/03
2. Contact Pins	PhBz Gold Plated	Checked by: <i>AKH</i>	Date: 04/5/03
Main Product: Top Entry Modular Jack 8P		Approved by: <i>AKH</i>	Date: 04/5/03
Tolerance: ± 0.2 mm	Scale: Not to scale	Drawing No: JP-T1-8P	
Dimensions: mm	3rd Angle Projection		



Pran Electronics Pvt. Ltd.
52 G.I.D.C. Makarpura
Vadodara 390 010.